


Your Intuitive, Reliable and All-Round office partner

Designed to operate in dynamic work environments and ensure consistent productivity. The TASKalfa 2554ci is one of the most reliable products in the field featuring cutting edge security and intelligent features that will help your business focus on what matters. The 10.1" touchscreen with our newly designed simple and intuitive user interface will make operating this as easy as possible.



Specifications

GENERAL

KYOCERATASKalfa Laser Colour Multifunctional, HyPASTM solution platform

Operation panel: 256.5 mm (10.1 inch) full-colour touch panel display, speaker for job notification, 15° - 90° swivel mounted Engine speed: Up to 25/12 pages A4/A3 per minute, Duplex print/copy speed: 24 pages A4 per minute

Resolution: 4800dpi equivalent x 1200dpi (print) 600 × 600 dpi (scan/copy)

Warm-up time: 18 seconds or less Time to first print: 7/9.2 seconds or less in Mono/Colour Time to first copy: 7.4/9.8 seconds or less in Mono/Colour (DP), approx. 6.4/8.5 or less in Mono/Colour (Platen)

CPU: ARM A53 (Quad Core) 1.6GHz Memory: Standard 4GB, 32GB SSD, Optional 320GB or 1TB Standard interfaces: USB 3.0 (Super-Speed USB), 4 x USB Host Interface, Gigabit Ethernet (10BaseT/100BaseTX/1000BaseT, IPv6, IPv4, IPSec, 802.3az support), optional Wi-Fi (IEEE 802.11a/b/g/n/ac), 2 eKUIO slots for optional internal print server or for optional fax system, slot for optional Wireless LAN, Slot for optional SD Card, NFC tag

Dimensions (W × D × H): 602mm × 665mm × 790mm

Weight: Approx. 90 kg

Power source: AC 220–240 V, 50/60 Hz Power consumption: Print Mode: 450 W; Copy Mode: 450 W;

Ready Mode: 40W; Sleep Mode: 0.5W
Noise (surface sound pressure level: ISO 7779 measurement

distance of 1 meter)
Copying/Printing Mode: 48.0 dB(A) LpA in colour

Stand-by: 31.4 dB(A) LpA
Safety standards: TÜV/GS, CE. This unit is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.

PAPER HANDLING

All paper capacities quoted are based on paper thickness of max. 0.11 mm. Please use paper recommended by Kyocera under normal environmental conditions.

Input capacity: Multi-purpose tray: 150 sheets, 52–300g/m², (Banner 136-163g/m 2), A6R - SRA3 (320 x 450 mm), Banner max. 304.8 x 1,220 mm, Standard universal paper cassette: 2 x 500 sheet 52 - 300g/m2, Upper cassette: A6R up to A4R, lower cassette A6R up to SRA3, Max. input capacity with options: 7,150 sheets A4

uplex: Standard supports 60–256g/m², SRA3 to A6R Output capacity: Standard 500 sheets face down, max. 5,000

PRINT FUNCTIONS

Controller language: PRESCRIBE Emulations: PCL6 (PCL5c/PCL-XL), KPDL3 (PostScript 3 compatible). PDF Direct Print, XPS Direct Print and OpenXPS Operating systems: All current Windows operating systems, MAC OS X Version 10.9 or higher, Unix, Linux, as well as other operating systems on request

Fonts/barcodes: 93 outline fonts (PCL), 136 fonts (KPDL 3), 4 fonts (Calibri), 4 fonts (Cambria), 1 Bitmap font, 45 types of

one-dimensional barcodes, 1 type of two-dimensional barcode (PDF417)

Print features: Encrypted PDF 2.0 Direct Print, IPP printing, e-mail printing, WSD print, secure printing via SSL, IPsec, SNMPv quick copy, proof and hold, private print, job storage and job management functionality, Super Resolution

Mobile printing support: AirPrint, Mopria, NFC, Direct Wi-Fi

(optional), MyPanel and KYOCERA Mobile Print app for iOS and

COPY FUNCTIONS

Max. original size: A3/Ledger Continuous copying: 1-9,999

Zoom range: 25–400% in 1% steps
Preset magnification ratios: 5 Reductions/5 Enlargements

Exposure mode: Manual: 17 steps

Image adjustments: Text + Photo, Photo, Text, Diagram/Map Features: Scan-once-copy-many, electronic sort, 2in1, 4in1, image repeat, page numbering, cover mode, booklet copy, interrupt copy, form overlay, margin shift, auto cassette change, skip blank page, ID copy, Handwriting erase and highlight

SCAN FUNCTIONS

Functionality: Scan-to-email. Scan-to-FTP Scan-to-SMB 3.0. Scan-to-USB Host, Scan-to-box, Network TWAIN, WSD scar (WIA Driver Network)

Scan speed: 200 ipm (300 dpi, A4, duplex, with DP-7160/7170) Scan resolution: 600, 400, 300, 200 dpi, 256 greyscales per colour Max. scan size: A3, Ledger

Original recognition: Text, photo, text + photo, Light Text / Fine Line, optimised for OCR

File types: TIFF, PDF, PDF/A, JPEG, Open XPS, Encrypted PDF, High compression PDF, PDF/A-1a/b, PDF/A-2a/b/u, Searchable PDF (option), MS Office file (option)

FAX FUNCTIONS (OPTIONAL)

Compatibility: ITUT Super G3 Modem speed: Max. 33.6 kbps

Transmission time: Less than 3 seconds (JBIG)

Scanning speed: 2.0 seconds or less

Maximum original size: A3/Ledger, Banner: 1,600mm

Compression method: JBIG, MMR, MR, MH Features: Network faxing, rotate transmission

rotate reception, encrypted transmission and reception, duplex fax reception, memory reception, mailbox, remote diagnostics, polling transmission and reception, broadcast, Optional Internetfax, dual fax with second fax system 12

CONSUMABLES

Average continuous toner yield in accordance with

TK-8365K Toner Kit: Microfine toner black for 25,000 pages A4

TK-8365C, TK-8365M, TK-8365Y Toner Kits: Microfine toner

cyan, magenta, yellow for 12,000 pages A4 \$ Staples: SH-10, 5000 x 3 staples, for BF-730, DF-7100, DF-7120 SH-12, 5000 x 3 staples, for DF-7140 $\,$

WT-8500: Waste Toner Bottle: 40,000 sheets (in accordance with 5% coverage, b/w: colour = 7:3)

OPTIONS

Internet Fax Kit (A) AC

Scan Extension Kit (A) AC: Scan to searchable PDF solution (embedded OCR), convert to PDF or MS Office (docx, xlsx, pptx) DP-7140: (Reversing), 50 sheets, 45–160 g/m2 (simplex), 50–120 g/m2 (duplex), A5R–A3, Banner up to 1,900 mm

DP-7150: (Reversing), 140 sheets, 35-160 g/m 2 (simplex), 50-120 g/m 2 (duplex), A6R-A3, Banner up to 1,900 mm

DP-7160: (one-path duplex scanning), 320 sheets at 50 - 80 g/m², 35–220 g/m² (simplex), 50–220 g/m² (duplex), A6R–A3, Banner

DP-7170: (one-path duplex scanning with ultrasonic sensor), 320 sheets at 50 - 80 g/m 2 , 35–220 g/m 2 (simplex), 50–220 g/m 2 (duplex), A6R–A3, Banner up to 1,900mm DT-730(B): Document tray

PF-7120: Side Deck: 3,000 sheets, A4, 60-300 g/m2

PF-7140: 2 x 500 sheets, 52–300 g/m2, A6R-SRA3 PF-7150: 2 x 1,500 sheets, A4, 52–300 g/m2, A4, B5, Letter

DF-7100: Inner finisher 500 sheets A4, 52–300 g/m2, A6R–SRA3 Stapling up to 50 sheets A4 or 30 sheets A3 at 3 positions DF-7120: 1,000 sheets A4, 52–300 g/m2, A6R–SRA3, Stapling up to 50 sheets A4 or 30 sheets A3 at 3 positions

DF-7140: Main tray: 4,000 sheets A4, Sub tray: 200 sheets A4, 52–300 g/m², A6R–SRA3, Stapling up to 65 sheets A4 or 30

sheets A3 at 3 positions
AK-7110 attachment kit for DF-7120 and DF-7140:

100 sheets, 52–300 g/m2, A6R–SRA3, Bridge unit AK-7110 is required when using a finisher PH-7C/PH-7D: Punch unit for DF-7120 and DF-7140 2-hole/4-hole/Swedish type, 45—300 g/m2, A5R—A3

MT-730(B): Mailbox sorter for DF-7140 7 bins x 100 sheets A4, 50 sheets A3/B4, 60-163 g/m2 BF-730: Booklet and tri-folding unit for DF-7140, Half-folding: 52–256 g/m2, A3, B4, A4R, Booklet: Max. 20 sheets (80 pages,

60–90 g/m2), Non-staple folding: Max. 5 sheets (60–90 g/m2) Tri-folding: Tri folding : Max 5 sheets (60–120 g/m2, A4R), Multi tri-folding: 5 sheets (60–90 g/m2), 3 sheets, (91–120 g/m2) JS-7100: 100-sheet internal job separator, 52-300 g/m2, A6R-SRA3

JS-7110: 250-sheet Inner shift tray, 52-300 g/m2, A6R-SRA3

PH-7120: Inner punch unit for inner finisher DF-7100 PH-7130: Inner punch unit for inner finisher DF-7100, Swedish type

HD-15: HDD 320 GB

HD-16: HDD 1 TB

NK-7120: NK-7120 Numeric keypad

UG-33 AC: Thin Print support

UG-34 AC: Emulation (IBM Proprinter/EPSON LQ-850/

USB IC Card Reader + Card Authentication Kit (B) AC

IB-37: Wireless Network Interface (USB: 5GHz/2.4GHz) IB-38: Wireless Network Interface (USB: 2.4GHz)

IB-50: GB-Ethernet board 10 BaseT/100 BaseTX/1,000 BaseT

IB-51: Wireless LAN Interface (802.11b/q/n)

Platen cover Type (E)

CB-7200W: Wooden cabinet CB-7210M: Metal cabinet

The TASKalfa 2554ci incorporates extremely durable components that guarantee efficient and reliable operation to meet the demanding requirements of busy office environments. The TASKalfa 2554ci provides effective productivity and maximum flexibility, whilst ensuring minimum impact on the environment.







KYOCERA Document Solutions Partner

KYOCERA Document Solutions (U.K.) Limited Eldon Court, 75-77 London Road Reading, Berkshire RG1 5BS Tel: 03330 151 855 Fax: 0118 931 1108

X KYOCERa

e: salesenquries@duk.kyocera.com

JANUARY2021DSTASKALFA2554CI/VER1.0