

Reliable and economical office workhorses

Economically attractive, the TASKalfa 2020 and 2320, B/W multifunctional printers are your highly reliable business partners. These printers are easy to operate via their straightforward operational panel. With their compact design, they virtually fit in any work environment and saves valuable office space. The devices offer exceptional high durability and deliver the professional quality that your business demands whenever you need it.



TASKalfa 2020 / TASKalfa 2320 — Specifications

GENERAL

KYOCERA TASKalfa Laser Monochrome

Operation panel:

2 Line LCD back light display with alphanumeric keypad

Engine speed: TASKalfa 2020:

up to 20 pages A4 per minute, up to 10 pages A3 per minute TASKalfa 2320:

up to 23 pages A4 per minute, up to 10 pages A3 per minute Resolution: Fast 1200 (1800 \times 600 dpi) print quality,

600 × 600 dpi (print/scan/copy)

Warm-up time: approx. 17.2 seconds or less Time to first print: approx. 5.7 seconds or less in b/w

Time to first copy: approx. 5.7 seconds or less in b/w CPU: ARM v5 base core equivalent, 500 MHz

Memory: 256 MB Standard interfaces: USB 2.0 (Hi-speed), 1 slot for optional SD

Card for service purpose
Integrated accounting: 10 department codes

Dimensions (W \times D \times H): Main unit: $565 \times 527 \times 455$ mm Weight: Main unit (including toner): approx. 27 kg

Power source: AC 220 - 240 V, 50/60 Hz

Power consumption:

TASKalfa 2020

Print mode/copy mode: 378 W

Ready mode: 74 W

TASKalfa 2320:

Print mode/copy mode: 450 W

Ready mode: 74 W

Sleep-mode: 1.1 W

Noise (sound pressure level: ISO 7779, measurement distance of 1 meter):

TASKalfa 2020:

Copying/Printing: 46.1dB(A) L_{pA}

Ready mode: 28.2dB(A) L

Sleep-mode: Not measurable

TASKalfa 2320:

Copying/Printing: 46.4 dB(A) L_{pA}

Ready mode: 27.4 dB(A) Lp.

ep-mode: Not measurable

Safety standards: TÜV/GS, CE. This unit is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.

PAPER HANDLING

All paper capacities quoted are based on paper thickness of max. 0.11mm. Please use paper recommended by Kyocera under normal environmental conditions.

Input capacity: Multi-purpose tray: 100 sheets, 45-160 g/m². A3, A4, A5, A6, Ledger, Letter, Legal;

Standard universal paper cassette: 300 sheets, 64-105 g/m², A3, A4, A5, Ledger, Letter, Legal;

Max. input capacity with options: 1,300 sheets A4 **Duplex:** Optional, 64–105 g/m², A3 to A5R Output capacity: Max. 250 sheets face-down

PRINT FUNCTIONS

Controller language: host-based (GDI) printing system Operating systems: Windows 8.1, Windows 10, Windows Server 2012/R2, Windows Server 2016, Windows Server 2019, Mac OS 10.5 or later, Linux

Print features: EcoPrint, Print Box with PIN Code protection, Poster Print, Multiple pages per sheet

Max. original size: A3/Ledger Continuous copying: 1 – 999 Zoom range: 25 – 400% in 1% steps

Preset magnification ratios: 5 Reductions/5 Enlargements

Image adjustments: Text + Photo, Photo, Text, Diagram/Map Features: scan-once-print-many, electronic sort copy, rotate sort copy¹, duplex copying², automatic paper selection³, layout mode (2-in-1, 4-in-1), border erase, binding margin, program key mode, ID card copy, interrupt copy

SCAN FUNCTIONS

Requires Windows Operating System and use of Client Tool Functionality: Scan-to-PC (SMB), scan-to-email application, TWAIN, WIA scan

Scan speed: up to 23 images per minute (600 dpi/A4)

Scan resolution: 600 dpi, 400 dpi, 300 dpi, 200 dpi, 256 greyscales per colour

Max. scan size: A3, Ledger

Original recognition: Text, photo, text + photo
File types: TIFF (MMR/JPEG Compression), PDF (MMR/JPEG Compression), High-compression PDF (CCITT Group 4/JBIG 2) JPEG, BMP, PNG

CONSUMABLES

Average continuous toner yield in accordance with 6% coverage A4.

Toner Kit TK-4145: toner black for 16,000 pages A4, capacity of starter toner is 3,000 pages A4

OPTIONS

DP-480 Document processor: (reversing) 50 sheets, $45-120\,\mathrm{g/m^2}$ (simplex), $50-120\,\mathrm{g/m^2}$ (duplex), A3-A5R, Ledger **DU-480 Duplex unit:** 64 – 105 g/m², A3 – A5R, Ledger **PF-480 Paper feeder:** 300 sheets, 64 – 105 g/m², A5R – A3, Ledger (max. $3 \times PF$ -480 can be added to the main system) Platen cover Type (H)

Cabinet: wooden/metal with desk storage capacity including castors (wheels)⁴

CB-480L: low wooden cabinet

CB-480H: high wooden cabinet⁴


CB-481L: low metal cabinet CB-481H: high metal cabinet⁴

- Paper feeder PF-480 is required
- Duplex unit DU-480 is required
- Document processor DP-480 is required
- Max. one cassette can be configured for high-type cabinet

The TASKalfa 2020/2320 incorporate durable components that guarantee efficient and reliable operation, to meet the demanding requirements of busy office environments. The TASKalfa 2020/2320 provide effective productivity and high flexibility whilst ensuring minimum impact on the environment.

KYOCERA Document Solutions (U.K.) Ltd **Eldon Court** 75-77 London Road Reading **Berkshire**

Tel: 0333 015 1855



JUNE2020DSTASKALFA2320/VER1.0

